

## Technical Specifications

<b>Product Name</b>	<b>PickUpPort™</b>
<b>Model Name</b>	<b>PickUpPort 1.0</b>
<b>Type</b>	PickUpPort Narrow: AS-99491 PickUpPort Wide: AS-99492
<b>Region</b>	Global
<b>Manufacturer</b>	AutoStore AS
<b>Dimensions</b>	PickUpPort Narrow: L: 1,475 mm / W: 595 mm / H: 1,385 mm PickUpPort Wide: L: 1,045 mm / W: 795 mm / H: 1,385 mm
<b>Weight</b>	PickUpPort Narrow: 90 kg PickUpPort Wide: 88 kg
<b>Weight Accuracy</b>	+/- 100 g
<b>Max. Load Including Bin</b>	35 kg
<b>Bin Height Support</b>	220, 330, and 425 mm
<b>Max. Bin Throughput</b>	170 Bins/hr. at full height Grid (6 meters) 5 seconds handling time
<b>Min. Exchange Time</b>	16 seconds at full height Grid (6 meters)
<b>Storage Temperature</b>	-25 °C to +55 °C
<b>Operating Temperature</b>	+2 °C to +40 °C
<b>Operating Humidity</b>	40 % to 90 % non-condensing
<b>Furniture Material</b>	Aluminum
<b>Working Height</b>	850 mm
<b>Noise Level</b>	<70 dBA
<b>Voltage</b>	24 VDC (110 – 240 VAC 50-60 Hz external supply)
<b>Max. Current</b>	1.6 A
<b>Power Consumption</b>	20 W
<b>Power Contact</b>	Kycon KPJX-4S-S
<b>Signal</b>	Ethernet, RJ45